

Glydea Ultra

PRODUCT SPECIFICATIONS

The silent and intelligent solution for curtain motorisation

PRODUCT MAIN FUNCTIONALITIES



Designed for silence

Silent mode and silent accessories.



Available in multiple technologies

RTS, DCT, WT and bi-directional technology with RS485 module. (to insert in RTS or DCT version)

RECOMMENDED TO SET WITH:

Universal test lead
(ref. 9 015 971)



Soft start and soft stop on RTS and DCT motors



Adjustable speed

5 speeds available.



Touch motion



Glydea Ultra

PRODUCT SPECIFICATIONS

BENEFITS FOR PROFESSIONALS

Reliable, robust and discreet

- The premium solution for residential and commercial projects

Adaptable & powerful

- Compatible with multiple technologies (WT/DCT/RTS/RS485) to meet the needs of smart buildings and smart homes
- Curtain weight up to 60kg

Flexible installation

- Available with inline connector for ease of programming
- Motor can fit either end of the track

BENEFITS FOR END USERS

Elegance

New design for the best aesthetic of the complete solution.

Comfort

Enjoy one of the quietest solutions on the market. Open and close smoothly to allow the right amount of light to create a perfect ambiance without disturbing your peace and quiet.

Smart and simple

Enjoy your smart home by controlling your curtains with Connexoon Window RTS and voice control (through IFTTT).

COMPATIBLE END-PRODUCTS



Curtains

TECHNICAL DATA

Thermal Time	2.5 minutes
Supply	AC
Index Protection Rating	IP30
Limit Switch Unit	Electronic
Temperature Working Range	0°C to +60°C
Electric Insulation	Class I

PERFORMANCE

End-limit Unit Versions Available	RTS*		DCT*		WT	
	35e	60e	35e	60e	35e	60e
Nominal Torque (nm)	0.6	1	0.6	1	0.6	1
Adjustable Linear Speed (cm/s)	20cm/s / 17.5cm/s / 15cm/s (default) / 12.5cm/s / 7.5cm/s (silent mode)					
Sound level (dBA)	45.2 / 43.4 / 39.7 / 37.3/ 29.8 dBA					
Voltage	230V /50Hz					
Maximum Current	0.4 A					
Radio Frequency (MHz)	433,42	433,42				
Adjustable Limits	Yes	Yes	Yes	Yes	Yes	Yes
Curtain Maximum Weight	35kg	60kg	35kg	60kg	35kg	60kg
Control Method	RTS		Dry contact via RJ12 socket		AC Switch	
L1 (mm)	348	348	348	348	348	348
Item Number	1240227	1240230	1240226	1240229	1240219	1240228
With inline connector	1241032	1241035	1241031	1241034	1241030	1241033
Dedicated RTS Wall Mounts for Curtain			Smooove 1 Open/Close Black RTS		1811009	
			Smooove 1 Open/Close White RTS		1811011	

*compatible with RS485 module (Ref 1870275).

